



Order no.: 120062

Mobile container hygienic type 2

Type

1

2

Specification

| | | | | |
|----------------------------------|-----------------------------------|-------------------------|--|-------------------------------------|
| Product type 2 | Length 1.2 m | Width 800 mm | Height 1.38 m | Max. load capacity 500 kg |
| Castor diameter 200 mm | Braking system Standard | Weight 100 kg | Business division MUNK Rettungstechnik | Article no. 120062 |

Facts

- Mobile container with "standard" undercarriage
- Washbasin (400 x 300 mm) made of stainless steel with tap and foot operation without hand contact
- Water inlet/outlet via quick coupling (transition piece to Storz-C, pressure reducer and waste water hose 5 m included)
- Hygiene board with soap and paper towel dispenser
- Universal dispenser for hand disinfection
- Integrated waste bin with flap
- 2 x Eurobox (600 x 400 x 235 mm) with lid
- 2 x Eurobox (600 x 400 x 285 mm) with lid
- 2 x Eurobox (600 x 400 x 335 mm) with lid

- Optionally available with food-safe hoses and continuous-flow heater
- Further sizes and versions available on request
- Optionally also available with "Quadro Light" undercarriage
- Scope of delivery without equipment items
- Series production quality equipment
- Stable and durable construction made of high-strength aluminium sections
- Platforms made of weatherproof wooden platform boards
- Ergonomic operation via continuous handle bar with non-slip and cold-insulating SoftGrip coating
- Robust and smooth-running actuating mechanism via flexible Bowden cable
- Two ball bearing castors Ø 200 mm with central wheel slewing arrestor for optimum handling
- Two ball bearing fixed castors Ø 200 mm with drum brake and dead man's function, resistant to dust, moisture and oil
- Foot-operated parking brake

Scope of supply

- Mobile container: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems

- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users


More product pictures



Added value

- The following equipment features are included as standard with every mobile container in the "Standard" assortment
- Body made of high-strength aluminium screw channel profile Connection of the profiles via stable, crossover corner screw connections – no welding!
- Markings for good visibility in the dark
- 2 fixed castors Ø 200 mm with internal drum brake and dead man's function
- 2 swivel castors Ø 200 mm with directional arrestors and central wheel and slewing arrestors
- Galvanised steel foot parking brake for swivel castors
- Operating control with ergonomic and continuous handle bars with SoftGrip coating
- Robust and smooth-running actuating mechanism via high-quality stainless steel Bowden cable

Accessories / Spare parts



Corporate certifications

on sustainability criteria

