

Order no.: 120911

Trolley for aluminium box



Specification

Length 1.2 m	Width 800 mm	Height 1.19 m	Height up to top edge of platform 293 mm	Height up to top edge of extension 813 mm
Max. load capacity 400 kg	Castor diameter 200 mm	Braking system Foot-operated parking brake	Castor type 2 swivel castors/2 fixed castors	Weight 70 kg
Business division MUNK Rettungstechnik	Article no. 120911			

Facts

- Transport trolley with aluminium box body
- Aluminium box tight-welded in the lower area (filling height: 200 mm, filling capacity: approx. 180 l)
- Right side wall lowered on one side for convenient loading and unloading
- Further sizes and versions available on request
- Scope of delivery without equipment items
- Series production quality equipment

- Stable and durable construction made of high-strength aluminium sections
- Ergonomic operation via continuous handle bar with non-slip cold-insulating SoftGrip coating
- Two ball bearing castors Ø 200 mm with central wheel slewing arrestor for optimum handling
- Two ball bearing fixed castors Ø 200 mm
- Foot-operated parking brake

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Corporate certifications

on sustainability criteria

